



61F-LS-CP11-SRA

Floatless level switch, plug-in, high functionality type, adjustable sensitivity, sequential operation, 11 pins, relay output, 100-240 VAC

Especificaciones

Application	Acid chemicals, Alkali chemicals, Distilled water, Liquids with high specific resistance, Liquids with low specific resistance, Salt water
Functions	Conductive level control
Features	Sequential operation
Cable length	4000 m
Installation type	Socket
Terminal	Plug-in
Size	41 mm
Supply voltage AC	100-240 V
Output type	Relay
Contact description	2 x SPDT
Body color	Black
Number of inputs for electrodes	3

Accesorios



BF-1

Portaelectrodos 150°C 1 polo cerámico



BF-3

Portaelectrodos 150°C 3 polos cerámicos













BF-5

Portaelectrodos 5 polos



BS-1

Portaelectrodos Alta presión 250°C 1 polo Teflón

	F03-11	Accesorio nivel
	F03-12	Accesorio nivel
	F03-14 1P	Accesorio nivel
	F03-14-3P	Accesorio nivel
	F03-14-5P	Accesorio nivel
	F03-60 SUS316	Accesorio Nivel
	PH-2 HAIPREN CODE 20M	Electrodo sumergido, cable de hipalón, cable de dos polos, 20 m de longitud
	PS-31 SUS304 1000MM	Portaelectrodos 3 polos juntos 1m
	PS-31 SUS304 300MM	Portaelectrodos 3 polos juntos 300mm
	PS-3S	Portaelectrodos 3 polos
	PS-4S	Portaelectrodos 4 polos
	PS-5S	Portaelectrodos 5 polos



PFC-N8

QUITAR DE TARIFA

Productos relacionados:



PF

La PF es la gama de conectores de la familia de relés MKS, también adecuados para los relés SSR y los productos de monitorización.