



A22EL-M-24A-11

Pulsador de parada de emergencia, iluminado 24 V ca/cc, 40 mm de diámetro, bloqueo al pulsar/desbloqueo al girar, SPST-NA + SPST-NC, IP65

Especificaciones

Number of contacts, normally-open	1
Number of contacts, normally-closed	1
Unlocking method	Turn unlatching mechanism
Diameter cap	40 mm
Hole diameter	22 mm
Mounting method	Built-in
With lighting	✓
With lock lever contact function	✗
Button text	None
Text colour	N/A
Lighting voltage	24 VAC/DC
Connection type auxiliary circuit	Screw connection
Degree of protection (IP)	IP65

Accesorios



A22-02

Bloque contactos 2NC



A22Z-3466-1

Placa PARADA EMERGENCIA 60 mm. diá.



A22Z-3905

Llave para tuercas



A22Z-B101Y

Caja 1 hueco A22 amarilla



A22Z-EG1

Cubierta para A22E con etiqueta EMERGENCY OFF

Descargas



Innovation in Control Panel Building
Catálogo

EN PDF 10 MB



Machine Safety
Catálogo

ES PDF 10 MB



Push Button Switches
Catálogo

EN PDF 20 MB



Pushbutton Switches
Catálogo

EN PDF 8 MB



Safety Component Selection Guide
Catálogo

EN PDF 10 MB



Safety Solution Advanced Guide
Guía

EN PDF 3 MB



Safety Solution Basic Guide
Guía

EN PDF 10 MB

TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 6 October, 2022. Haga clic aquí para acceder a los [legal](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU