



E3FC-TP21

Inox Barrera 20m PNP Conector M12

Especificaciones

| | |
|----------------------------------|-------------------------|
| Shape | Cylindrical axial |
| Sensing method | Through-beam |
| Sensing distance | 20000 mm |
| Setting method | Manual adjustment |
| Connection method | Connector M12 |
| Output type | PNP |
| Operation mode | Dark-ON, Light-ON |
| Response time | 0.5 ms |
| Material housing | Stainless steel |
| Thread size | M18 |
| Length | 48 mm |
| Type of light | Polarity free red light |
| Power supply voltage | 10-30 V |
| Degree of protection (IP) | IP67/IP69K |

Accesorios



E39-L183

Soporte de montaje metálico para E3FA

Productos relacionados:



Conectores y juegos de cables M12

Juegos de cables y conectores industriales para cualquier aplicación

Descargas

Librería CAD



E3FC Photoelectric Sensors, M18 Stainless steel housing

Datasheet

EN PDF 2 MB

TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 18 August, 2022. Haga clic aquí para acceder a los [legal](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU