



## E3Z-LL83 0.5M

Photoelectric sensor, rectangular housing, red laser class 1, background suppression, high speed version, 300 mm, PNP, Light-ON/Dark-ON, 0.5 m cable

# Especificaciones

<b>Shape</b>	Cuboid
<b>Sensing method</b>	Background suppression
<b>Sensing distance</b>	300 mm
<b>Sensing distance (min.)</b>	25 mm
<b>Setting method</b>	Manual adjustment
<b>Connection method</b>	Cable
<b>Cable length</b>	0.5 m
<b>Output type</b>	PNP
<b>Operation mode</b>	Dark-ON, Light-ON
<b>Response time</b>	0.5 ms
<b>Material housing</b>	PBT
<b>Thread size</b>	Other
<b>Width</b>	10.8 mm
<b>Height</b>	31 mm
<b>Depth</b>	20 mm
<b>Type of light</b>	Laser diode, red light
<b>Laser class</b>	1
<b>Spot size</b>	0.5 mm
<b>Power supply voltage</b>	12-24 V
<b>Features</b>	High precision positioning & detection
<b>Degree of protection (IP)</b>	IP67



**E39-L104**

Soporte montaje para E3Z y E32-R21



**E39-L142**

Soporte de montaje ranurado para E3Z Tornillos M3



**E39-L144**

Soporte de montaje y protección para E3Z Tornillos



**E39-L150**

Soporte de montaje ajuste vertical E3Z/E3S-R 65mm



**E39-L151**

Soporte de montaje ajuste vertical E3Z/E3S-R 165mm



**E39-L153**

Soporte de montaje E3Z. Tornillo ranura M3x8



**E39-L43**

Soporte montaje horizontal E3Z



**E39-L44**

Soporte de montaje posterior E3Z



**E39-L98**

Soporte montaje para E3Z y E3S-R6

## Librería CAD



### E3Z Catálogo

ES PDF 1 MB



### E3Z Laser Series Datasheet

ES PDF 1 MB



### E3Z-L\_\_\_\_ Introducción

EN PDF 300 KB