



MY4-GS 24VAC

Relé, enchufable, 14 contactos, 4PDT, 3 A, indicador mecánico, 24 V ca

Transparent case	✓
With mechanical indicator	✓
Mounting method	With plug-in socket
Usage	General purpose
Poles	4
Rated carry current	6 A
Coil voltage	24 V
Operation voltage	AC
Contact material	Ag
Contact description	4PDT
Terminal	Plug-in, Solder

También se ajusta a



PYF-14-PU

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals



PYF-14-PU-L

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals,



PYF14-ESN-B

Socket, with common and coil terminals on the bottom and with the NC & NO terminal on the top - Black.



PYF14-ESS-B

Socket, with common, NC & NO terminals at the top and the coil terminals at the bottom - Black



PYF14S

Socket, DIN rail mounting, 14-pin, screwless terminals



PYFZ-14-E

Socket, DIN rail/surface mounting, 14-pin, screw terminals (standard)

Descargas



Industrial Relays Catálogo

ES PDF 2 MB



MY-GS Datasheet

EN PDF 5 MB



MY-GS Miniature Power Relays Catálogo

EN PDF 1 MB



The Problem-and- Solution case Environment resistance

Catálogo

EN PDF 600 KB

TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 28 January, 2023. Haga clic aquí para acceder a los [legal](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU