



MY4IN 24VDC (S)

4PDT 5A Enchuf./soldar LED Indic. Pulsador prueba

Especificaciones

Transparent case	✓
With mechanical indicator	✓
Mounting method	With plug-in socket
Usage	General purpose
Poles	4
Rated carry current	5 A
Coil voltage	24 V
Operation voltage	DC
Contact material	Ag alloy + Au cladding
Contact description	4PDT
Features	LED, Test button
Terminal	Plug-in, Solder

También se ajusta a



PYF-14-PU

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals



PYF14S

Socket, DIN rail mounting, 14-pin, screwless terminals

Librería CAD



Industrial Relays Catálogo

ES PDF 2 MB



MY Miniature Power Relays Catálogo

EN PDF 1 MB



MY Miniature Power Relays - MY/MYK/MYQ-MYH Datasheet

EN PDF 20 MB



MY(S) Miniature Power Relays Datasheet

EN PDF 10 MB



MY-GS Datasheet

EN PDF 5 MB

TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 18 August, 2022. Haga clic aquí para acceder a los [legal](#).