



MY4IN1 100/110VDC (S)

4PDT 5A Ench/soldar Inversa Indic. Puls. prueba

Mounting method	With plug-in socket
Usage	General purpose
Poles	4
Rated carry current	5 A
Coil voltage	110 V
Operation voltage	DC
Contact material	Ag alloy + Au cladding
Contact description	4PDT
Features	LED, Reverse coil polarity, Test button, Transparent case, With mechanical indicator
Terminal	Plug-in, Solder



PYF-14-PU

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals



PYF-14-PU-L

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals,



PYF14-ESN-B

Socket, with common and coil terminals on the bottom and with the NC & NO terminal on the top - Black.



PYF14-ESS-B

Socket, with common, NC & NO terminals at the top and the coil terminals at the bottom - Black



PYF14S

Socket, DIN rail mounting, 14-pin, screwless terminals



PYFZ-14-E

Socket, DIN rail/surface mounting, 14-pin, screw terminals (standard)

Librería CAD



Industrial Relays Catálogo

ES PDF 2 MB



MY(S) Miniature Power Relays Datasheet

EN PDF 9 MB



MY-GS Miniature Power Relays Catálogo

EN PDF 1 MB



OMRON Manufacturing Know-How: High Quality Relays

Folleto

EN PDF 400 KB



The Problem-and- Solution case Environment resistance Catálogo

EN PDF 600 KB