



## MY4N 48VDC (S)

4PDT 5A indicador Enchuf/soldar

<b>Transparent case</b>	✓
<b>With mechanical indicator</b>	✓
<b>Mounting method</b>	With plug-in socket
<b>Usage</b>	General purpose
<b>Poles</b>	4
<b>Rated carry current</b>	5 A
<b>Coil voltage</b>	48 V
<b>Operation voltage</b>	DC
<b>Contact material</b>	Ag alloy + Au cladding
<b>Contact description</b>	4PDT
<b>Features</b>	LED
<b>Terminal</b>	Plug-in, Solder

# También se ajusta a



## **PYF-14-PU**

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals



## **PYF-14-PU-L**

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals,



## **PYF14-ESN-B**

Socket, with common and coil terminals on the bottom and with the NC & NO terminal on the top - Black.



## **PYF14-ESS-B**

Socket, with common, NC & NO terminals at the top and the coil terminals at the bottom - Black



## **PYF14S**

Socket, DIN rail mounting, 14-pin, screwless terminals



## **PYFZ-14-E**

Socket, DIN rail/surface mounting, 14-pin, screw terminals (standard)

## Librería CAD



### Industrial Relays Catálogo

ES PDF 2 MB



### MY Miniature Power Relays Catálogo

EN PDF 1 MB



### MY Miniature Power Relays - MY/MYK/MYQ-MYH Datasheet

EN PDF 20 MB



### MY(S) Miniature Power Relays Datasheet

EN PDF 10 MB



### MY-GS Datasheet

EN PDF 5 MB

#### TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 6 October, 2022. Haga clic aquí para acceder a los [legal](#).