



## MY4N-GS 220/240VAC

Relé, enchufable, 14 contactos, 4PDT, 3 A, indicadores mecánicos y LED, 220/240 V ca

<b>Transparent case</b>	✓
<b>With mechanical indicator</b>	✓
<b>Mounting method</b>	With plug-in socket
<b>Usage</b>	General purpose
<b>Poles</b>	4
<b>Rated carry current</b>	6 A
<b>Coil voltage</b>	230 V
<b>Operation voltage</b>	AC
<b>Contact material</b>	Ag
<b>Contact description</b>	4PDT
<b>Features</b>	LED
<b>Terminal</b>	Plug-in, Solder

# También se ajusta a



## PYF-14-PU

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals



## PYF-14-PU-L

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals,



## PYF14-ESN-B

Socket, with common and coil terminals on the bottom and with the NC & NO terminal on the top - Black.



## PYF14-ESS-B

Socket, with common, NC & NO terminals at the top and the coil terminals at the bottom - Black



## PYF14S

Socket, DIN rail mounting, 14-pin, screwless terminals



## PYFZ-14-E

Socket, DIN rail/surface mounting, 14-pin, screw terminals (standard)

## Descargas

Librería CAD



### Industrial Relays Catálogo

ES PDF 2 MB



### MY Miniature Power Relays Catálogo

EN PDF 1 MB



### MY-GS Datasheet

EN PDF 5 MB

## TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 18 August, 2022. Haga clic aquí para acceder a los [legal](#).

**OMRON**

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU