



MY4ZN 110/120VAC (S)

4PDT bifurcado 5A indicador Enchuf/soldar

| | |
|----------------------------------|--------------------------|
| Transparent case | ✓ |
| With mechanical indicator | ✓ |
| Mounting method | With plug-in socket |
| Usage | General purpose |
| Poles | 4 |
| Rated carry current | 5 A |
| Coil voltage | 110 V |
| Operation voltage | AC |
| Contact description | 4PDT |
| Features | Bifurcated contacts, LED |
| Terminal | Plug-in |



PYF-14-PU

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals



PYF-14-PU-L

Socket, DIN rail/surface mounting, 31 mm, 14-pin, Push-in terminals,



PYF14-ESN-B

Socket, with common and coil terminals on the bottom and with the NC & NO terminal on the top - Black.



PYF14-ESS-B

Socket, with common, NC & NO terminals at the top and the coil terminals at the bottom - Black



PYF14S

Socket, DIN rail mounting, 14-pin, screwless terminals



PYFZ-14-E

Socket, DIN rail/surface mounting, 14-pin, screw terminals (standard)

Librería CAD



Industrial Relays Catálogo

ES PDF 2 MB



MY Miniature Power Relays Catálogo

EN PDF 1 MB



MY Miniature Power Relays - MY/MYK/MYQ-MYH Datasheet

EN PDF 20 MB



MY(S) Miniature Power Relays Datasheet

EN PDF 10 MB



MY-GS Datasheet

EN PDF 5 MB

TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 18 August, 2022. Haga clic aquí para acceder a los [legal](#).