



## P2RF-08-ESS

Base G2R-2-S 8 pines Carril DIN PRO

# Especificaciones

Applicable product family	G2R-2-S
Mounting method	DIN rail/screw
Depth	61 mm
Height	77.6 mm
Width	15.6 mm
Terminal	Rise-up
Color	Black
Hold down clip included	✘
Release Lever included	✘
Applicable wire	Solid, Stranded, With ferrules
Applicable ferrules	Forked terminals, Round terminals

## También se ajusta a



**G2R-2-S 110VAC (S)**  
Relay, plug-in, DPDT, 5 A,  
mechanical indicator, 110  
VAC



**G2R-2-S 12VDC (S)**  
Relay, plug-in, 8-pin, DPDT,  
10 A, mech indicator, label  
facility, 12 VDC



**G2R-2-S 220VAC (S)**  
Relay, plug-in, 5 A,  
mechanical indicator, 220  
VAC



**G2R-2-S 230VAC (S)**  
Relay, plug-in, DPST, 10 A,  
mechanical indicator, 230  
VAC

**G2R-2-S 240VAC (S)**

Relay, plug-in, DPDT, 5 A, mechanical indicator, 240 VAC

**G2R-2-S 24VAC (S)**

Relay, plug-in, DPDT, 5 A, mechanical indicator, 24 VAC

**G2R-2-S 48VDC (S)**

Relay, plug-in, DPDT, 5 A, mechanical indicator, 48 VDC

**G2R-2-SD 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech indicators, coil suppressor, label facility

**G2R-2-SN 110VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 110 VDC

**G2R-2-SN 120VAC (S)**

Relay, plug-in, DPDT, 5 A, mech. & LED indicator, 120 VAC

**G2R-2-SN 12VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 12 VAC

**G2R-2-SN 240VAC (S)**

Relay, plug-in, DPDT, 5 A, mech. & LED indicator, 240 VAC

**G2R-2-SN 48VAC**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, label facility, 48 VAC

**G2R-2-SN-AP3 230VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, gold-plated contacts, LED indicator

**G2R-2-SN-AP3 24VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, gold-plated contacts, LED indicator

**G2R-2-SND 48VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, label facility, 48 VDC

**G2R-2-SNDI 48VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, coil suppressor, lockable test button, label facility

**G2R-2-SNDI-AP3 24VDC (S)**

Relay, plug-in, 8-pin, SPDT, 5 A, mech & LED indicators, coil suppressor, label test button, Au-plating

**G2R-2-SNI 110VAC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility

**G2R-2-SNI 120VAC (S)**

Relay, plug-in, DPDT, 5 A, mech. & LED indicator, test button, 120 VAC

**G2R-2-SNI 240VAC (S)**

Relay, plug-in, DPDT, 5 A, mech. & LED indicator, test button, 240 VAC

**G2R-2-SNI 48VDC (S)**

Relay, plug-in, 8-pin, DPDT, 5 A, mech & LED indicators, lockable test button, label facility

**G2R-2-SNI-AP3 230VAC (S)**

Relay, plug-in, DPDT (gold plated), 5 A, mech. & LED indicator, test button, 230 VAC

## Accesorios

**P2CM-ESS**

Clip & release lever for P2RF-\*\*-ESS socket (1 pc = 1 bag including 10 levers)

**PFP-100N**

DIN-rail mounting track, 35x7.3mm, 1m length.

**PFP-100N2**

Carril DIN 100cm mayor grosor

**PFP-50N**

Carril DIN 50cm

**PFP-M**

Carril DIN

**PFP-S**

Spacer

**PYC-TR**

Placa de identificación para la toma P2RF-\*\*-ESS (1 unidad = 1 bolsa incluye 10 placas)

**XW5Z-EP12**

Placa separadora para bornes de carril DIN, 12 mm ancho

**XW5Z-EP6**

Placa separadora para bornes de carril DIN, 6 mm ancho

Librería CAD



## P2RF-08-ESS Relay Sockets

Datasheet

EN PDF 500 KB