



## PYF-14-PU-L

Base MY Carril DIN 14 pines Push-in+

# Especificaciones

Applicable product family	H3YN, MY2K, MY4, MY4-GS
Mounting method	DIN rail/screw
Terminal	Push-in Plus
Width	31 mm
Height	90 mm
Depth	52.1 mm
Color	Black
Hold down clip included	×
Release Lever included	×
Applicable wire	Solid, Stranded, With ferrules
Applicable ferrules	Round terminals
Hold down clip for relay with CR circuit	Y92H-3

## También se ajusta a



### MY4 100/110VDC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech indicator, label facility, 100/110 VDC



### MY4 48/50VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech indicator, label facility, 48/50 VAC



### MY4 48VDC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech indicator, label facility, 48 VDC



### MY4-GS 220/240VAC

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 220/240 VAC

**MY4-GS 24VAC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 24 VAC

**MY4-GS 24VDC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 24 VDC

**MY4IN 100/110VDC (S)**

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, lockable push to test button, label facility, 100/110 VDC

**MY4IN 48VDC (S)**

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, lockable push to test button, label facility

**MY4IN-CR 110/120VAC (S)**

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, coil suppressor, lockable push to test button, label facility, 100/120 VAC

**MY4IN-D2-GS 24VDC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, coil suppressor, lockable push test button, 24 VDC

**MY4IN-GS 110/120VAC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 110/120 VAC

**MY4IN-GS 220/240VAC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 220/240 VAC

**MY4IN-GS 24VAC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 24 VAC

**MY4IN-GS 24VDC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 24 VDC

**MY4IN1 100/110VDC (S)**

Relay, plug-in, 14-pin, 4PDT, reverse coil polarity, 5 A, mech & LED indicators, lockable push to test button, label facility, 100/110 VDC

**MY4IN1 12VDC (S)**

Relay, plug-in, 14-pin, 4PDT, reverse coil polarity, 5 A, mech & LED indicators, lockable push to test button, label facility,

**MY4N 100/110VDC (S)**

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, label facility, 100/110 VDC

**MY4N 110/120VAC (S)**

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, label facility, 110/120 VAC

**MY4N 48/50VAC (S)**

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, label facility, 48/50 VAC

**MY4N 48VDC (S)**

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, label facility, 48 VDC



### MY4N-CR 110/120VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, coil suppressor, label facility, 110/120 VAC



### MY4N-D2 12VDC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, coil suppressor, label facility, 12 VDC



### MY4N-D2-GS 12VDC

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, coil suppressor, 12 VDC

### MY4N-D2-GS 24VDC

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, coil suppressor, 24 VDC



### MY4N-GS 220/240VAC

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, 220/240 VAC



### MY4N-GS 24VDC

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, 24 VDC



### MY4N-GS 48VDC

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, label facility, 48 VDC



### MY4N1 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, reverse coil polarity, 5 A, mech & LED indicators, label facility, 24 VDC



### MY4N1-D2 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, reverse coil polarity, 5 A, mech & LED indicators, coil suppressor, label facility, 24 VDC



### MY4Z 24VDC (S)

Relay, plug-in, 14-pin, bifurcated contacts, 4PDT, 5 A, mech indicator, label facility, 24 VDC



### MY4ZIN1 24VDC (S)

Relay, plug-in, 4PDT (bifurcated), reverse coil polarity, 3 A, mech. + LED indicator, test button, 24 VDC



### MY4ZN 110/120VAC (S)

Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, label facility, 110/120 VAC



### MY4ZN 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, label facility, 24 VDC



### MY4ZN-D2 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, coil suppressor label facility, 24 VDC

## Accesorios



**MG-CPM-04 41390N**

Hojas modulares con 48 marcadores de 5x10 mm, policarbonato, sin halógenos, sin silicona, UL94 V0, -40 a 130 °C, pedido mínimo: 1 caja (cada caja contiene 35 hojas, 1680 marcadores en total)

**PFP-100N**

DIN-rail mounting track, 35x7.3mm, 1 m length.

**PFP-100N2**

Carril DIN 100cm mayor grosor

**PFP-50N**

Carril DIN 50cm



**PFP-M**

Carril DIN

**PFP-S**

Espaciador bases de relés para carril DIN



**PYC-A1**

Clip para bases Carril DIN



**PYDN-31.0-080R**

Puente de conexión para PYF-PU Paso 31mm 8 Polos Rojo



**PYDN-31.0-080S**

Puente de conexión para PYF-PU Paso 31mm 8 Polos Azul



**PYDN-31.0-080Y**

Puente de conexión para PYF-PU Paso 31mm 8 Polos Amarillo



**PYDN-7.75-020R**

Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 2 Polos Rojo
















**PYDN-7.75-020S**

Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 2 Polos Azul



**PYDN-7.75-020Y**

Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 2 Polos Amarillo

	<b>PYDN-7.75-030R</b>	Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 3 Polos Rojo
	<b>PYDN-7.75-030S</b>	Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 3 Polos Azul
	<b>PYDN-7.75-030Y</b>	Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 3 Polos Amarillo
	<b>PYDN-7.75-040R</b>	Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 4 Polos Rojo
	<b>PYDN-7.75-040S</b>	Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 4 Polos Azul
	<b>PYDN-7.75-040Y</b>	Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 4 Polos Amarillo
	<b>PYDN-7.75-200R</b>	Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 20 Polos Rojo
	<b>PYDN-7.75-200S</b>	Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 20 Polos Azul
	<b>PYDN-7.75-200Y</b>	Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 20 Polos Amarillo
	<b>XW5Z-EP12</b>	Placa separadora para bornes de carril DIN, 12 mm ancho
	<b>XW5Z-EP6</b>	Placa separadora para bornes de carril DIN, 6 mm ancho
	<b>Y92F-78</b>	Adaptador frontal para H3Y
	<b>Y92H-3</b>	Clip sujeción para PYF08A/-N y PYF14A/-N

Librería CAD



## PYF-\_-PU/P2RF-\_-PU Datasheet

EN PDF 3 MB