



PYF-14-PU

Base MY Carril DIN 14 pines Palanca de expulsión Push-in+

Especificaciones

Applicable product family	H3YN, MY2K, MY4, MY4-GS
Mounting method	DIN rail/screw
Terminal	Push-in Plus
Product Width (unpacked)	31 mm
Product Height (unpacked)	90 mm
Product Depth (unpacked)	67.5 mm
Color	Black
Hold down clip included	✓
Release Lever included	✓
Applicable wire	Solid, Stranded, With ferrules
Applicable ferrules	Round terminals

También se ajusta a



MY4 100/110VDC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech indicator, label facility, 100/110 VDC



MY4 110/120VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech indicator, label facility, 110/120 VAC



MY4 12VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech indicator, label facility, 12 VAC



MY4 12VDC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech indicator, label facility, 12 VDC

TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 25 March, 2023. Haga clic aquí para acceder a los [legal](#).



MY4 220/240VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech indicator, label facility



MY4 24VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech indicator, label facility



MY4 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech indicator, label facility



MY4 48/50VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech indicator, label facility, 48/50 VAC



MY4 48VDC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech indicator, label facility, 48 VDC



MY4-GS 12VAC

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 12 VAC



MY4-GS 12VDC

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 12 VDC



MY4-GS 48VDC

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 48 VDC



MY4-GS-R AC12

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 12 VAC



MY4-GS-R AC220/240

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 220/240 VAC



MY4-GS-R AC24

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 24 VAC



MY4-GS-R DC12

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 12 VDC



MY4-GS-R DC24

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 24 VDC



MY4-GS-R DC48

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 48 VDC



MY4H 100/110VDC

Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, 110 VAC



MY4H 110/120VAC

Relay, plug-in, 14-pin, 4PDT, 3 A, hermetically-sealed

TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 25 March, 2023. Haga clic aquí para acceder a los [legal](#).



MY4H 12VDC

Relay, plug-in, 14-pin, 4PDT, 3 A, hermetically-sealed



MY4H 24VAC

Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, 24 VAC



MY4H 24VDC

Relay, plug-in, 14-pin, 4PDT, 1 A, hermetically-sealed



MY4H 48VDC

Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, 48 VDC



MY4H-0 24VDC

Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, 24 VDC



MY4IN 100/110VDC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, lockable push to test button, label facility, 100/110 VDC



MY4IN 110/120VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, test button, label facility



MY4IN 12VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, lockable push to test button, label facility, 12 VAC



MY4IN 12VDC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, lockable push to test button, label facility



MY4IN 220/240VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, lockable push to test button, label facility



MY4IN 24VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, test button, label facility



MY4IN 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, lockable push to test button, label facility



MY4IN 48/50VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, lockable push to test button, label facility



MY4IN 48VDC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, lockable push to test button, label facility



MY4IN-CR 110/120VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, coil suppressor, lockable push to test button, label facility, 100/120 VAC



MY4IN-CR 220/240VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, coil suppressor, lockable push to test button, label facility, 220/240 VAC VDC

TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 25 March, 2023. Haga clic aquí para acceder a los [legal](#).

**MY4IN-CR-GS
220/240VAC**

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, coil
suppressor, lockable push
test button. 220/240 VAC

**MY4IN-CR-GS-R
AC220/240**

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, coil
suppressor, lockable push
test button. 220/240 VAC

**MY4IN-D2 12VDC (S)**

Relay, plug-in, 14-pin,
4PDT, 5 A, mech & LED
indicators, coil suppressor,
lockable push to test button,
label facility, 12 VDC

**MY4IN-D2 24VDC (S)**

Relay, plug-in, 14-pin,
4PDT, 5 A, mech & LED
indicators, coil suppressor,
lockable push to test button,
label facility, 24 VDC

**MY4IN-D2-GS 48VDC**

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, coil
suppressor, lockable push
test button, 48 VDC

**MY4IN-D2-GS-R DC24**

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, coil
suppressor, lockable push
test button, 24 VDC

**MY4IN-GS
100/110VDC**

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, lockable
push test button, 100/110
VDC

**MY4IN-GS 12VDC**

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, lockable
push test button, 12 VDC

**MY4IN-GS 48VDC**

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, lockable
push test button, 48 VDC

**MY4IN-GS-R
AC110/120**

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, lockable
push test button, 110/120
VAC

**MY4IN-GS-R
AC220/240**

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, lockable
push test button, 220/240
VAC

**MY4IN-GS-R AC24**

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, lockable
push test button, 24 VAC

**MY4IN-GS-R
DC100/110**

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, lockable
push test button, 100/110
VDC

**MY4IN-GS-R DC12**

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, lockable
push test button, 12 VDC

**MY4IN-GS-R DC24**

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, lockable
push test button, 24 VDC

**MY4IN-GS-R DC48**

Relay, plug-in, 14-pin,
4PDT, 6 A, mechanical &
LED indicators, lockable
push test button, 48 VDC

TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 25 March, 2023. Haga clic aquí para acceder a los [legal](#).



MY4IN1 100/110VDC (S)

Relay, plug-in, 14-pin, 4PDT, reverse coil polarity, 5 A, mech & LED indicators, lockable push to test button, label facility. 100/110 VDC



MY4IN1 12VDC (S)

Relay, plug-in, 14-pin, 4PDT, reverse coil polarity, 5 A, mech & LED indicators, lockable push to test button, label facility,



MY4IN1 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, reverse coil polarity, 5 A, mech & LED indicators, lockable push to test button, label facility,



MY4IN1-D2 12VDC (S)

Relay, plug-in, 14-pin, 4PDT, reverse coil polarity, 5 A, mech & LED indicators, coil suppressor, lockable push to test button, label facility, 12 VDC



MY4IN1-D2 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, reverse coil polarity, 5 A, mech & LED indicators, coil suppressor, lockable push to test button, label facility, 24 VDC



MY4N 100/110VDC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, label facility, 100/110 VDC



MY4N 110/120VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, label facility, 110/120 VAC



MY4N 12VDC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, label facility, 12 VDC



MY4N 220/240VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, label facility, 220/240 VAC



MY4N 24VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, label facility, 24 VAC



MY4N 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, label facility, 24 VDC



MY4N 48/50VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, label facility, 48/50 VAC



MY4N-CR 110/120VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, coil suppressor, label facility, 110/120 VAC



MY4N-CR 220/240VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, coil suppressor, label facility, 220/240 VAC



MY4N-CR-GS 220/240VAC

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, coil suppressor, 220/240 VAC



MY4N-D2 12VDC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, coil suppressor, label facility, 12 VDC

TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 25 March, 2023. Haga clic aquí para acceder a los [legal](#).



MY4N-D2 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, coil suppressor, label facility, 24 VDC



MY4N-D2-GS 12VDC

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, coil suppressor, 12 VDC



MY4N-D2-GS 24VDC

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, coil suppressor, 24 VDC



MY4N-GS 12VDC

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, 12 VDC



MY4N-GS 220/240VAC

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, 220/240 VAC



MY4N-GS 220VDC

Relay, plug-in, 14-pin, 4PDT, 3 A, mechanical & LED indicators, 220 VDC



MY4N-GS 24VDC

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, 24 VDC



MY4N-GS 48VDC

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, label facility, 48 VDC



MY4N1 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, reverse coil polarity, 5 A, mech & LED indicators, label facility, 24 VDC



MY4N1-D2 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, reverse coil polarity, 5 A, mech & LED indicators, coil suppressor, label facility, 24 VDC



MY4Z 110/120VAC (S)

Relay, plug-in, 14-pin, bifurcated contacts, 4PDT, 5 A, mech indicator, label facility, 100/120 VAC



MY4Z 220/240VAC (S)

Relay, plug-in, 14-pin, bifurcated contacts, 4PDT, 5 A, mech indicator, label facility, 220/240 VAC



MY4Z 24VDC (S)

Relay, plug-in, 14-pin, bifurcated contacts, 4PDT, 5 A, mech indicator, label facility, 24 VDC



MY4ZH 100/110VAC

Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, bifurcated contacts, 110 VAC



MY4ZH 24VAC

Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, bifurcated contacts, 24 VAC



MY4ZH 24VDC

Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, bifurcated contacts

TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 25 March, 2023. Haga clic aquí para acceder a los [legal](#).



MY4ZIN 24VDC (S)

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, test button, 24 VDC



MY4ZIN1 24VDC (S)

Relay, plug-in, 4PDT (bifurcated), reverse coil polarity, 3 A, mech. + LED indicator, test button, 24 VDC



MY4ZN 220/240VAC (S)

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, 220/240 VAC



MY4ZN 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, label facility, 24 VDC



MY4ZN-D2 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, coil suppressor label facility, 24 VDC



MYQ4 110/120VAC

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, 110/120 VAC



MYQ4 220/240VAC

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, 220/240 VAC



MYQ4 24VDC

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, 24 VDC



MYQ4N 110/120VAC

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, with indicator, 110/120 VAC



MYQ4N 220/240VAC

Plastic sealed relay, plug-in, 14-pin, 4PDT, 1 A, with LED, 220/240 VAC



MYQ4N 24VAC

Plastic sealed relay, plug-in, 14-pin, 4PDT, 1 A, with LED, 24 VAC



MYQ4N 24VDC

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, with indicator, 24 VDC



MYQ4N-D2 24VDC

Plastic sealed relay, plug-in, 14-pin, 4PDT, 1 A, with LED, 24 VDC



MYQ4Z 200/220VAC

Plastic sealed relay, plug-in, 14-pin, 4PDT, 1 A, bifurcated contacts

Accesorios

TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 25 March, 2023. Haga clic aquí para acceder a los [legal](#).



MG-CPM-04 41390N

Hojas modulares con 48 marcadores de 5x10 mm, policarbonato, sin halógenos, sin silicona, UL94 V0, -40 a 130 °C, pedido mínimo: 1 caja (cada caja contiene 35 hojas, 1680 marcadores en total)

PFP-100N

DIN-rail mounting track, 35x7.3mm, 1 m length.

PFP-100N2

Carril DIN 100cm mayor grosor

PFP-50N

Carril DIN 50cm



PFP-M

Carril DIN

PFP-S

Espaciador bases de relés para carril DIN



PYDN-15.5-080R

Puente de conexión para P2RF-PU Paso 15.5mm 8 Polos Rojo



PYDN-31.0-080S

Puente de conexión para PYF-PU Paso 31mm 8 Polos Azul



PYDN-31.0-080Y

Puente de conexión para PYF-PU Paso 31mm 8 Polos Amarillo



PYDN-7.75-020R

Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 2 Polos Rojo



PYDN-7.75-020S

Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 2 Polos Azul



PYDN-7.75-020Y

Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 2 Polos Amarillo



PYDN-7.75-030R

Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 3 Polos Rojo


TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 25 March, 2023. Haga clic aquí para acceder a los [legal](#).



PYDN-7.75-030S

Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 3 Polos Azul



PYDN-7.75-030Y

Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 3 Polos Amarillo



PYDN-7.75-040R

Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 4 Polos Rojo



PYDN-7.75-040S

Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 4 Polos Azul



PYDN-7.75-040Y

Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 4 Polos Amarillo



PYDN-7.75-200R

Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 20 Polos Rojo



PYDN-7.75-200S

Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 20 Polos Azul



PYDN-7.75-200Y

Puente de conexión para P2RF-PU/PYF-PU Paso 7.75mm 20 Polos Amarillo



XW5Z-EP12

Placa separadora para bornes de carril DIN, 12 mm ancho



XW5Z-EP6

Placa separadora para bornes de carril DIN, 6 mm ancho



Y92H-3

Clip sujeción para PYF08A/-N y PYF14A/-N

Librería CAD



PYF-PU/PTF-PU/P2RF-PU Sockets with Push-In Plus technology

Datasheet

EN PDF 3 MB