



PYF14-ESN-B

Conector, con terminales comunes y de muelle en la parte inferior y con terminales NC y NA en la parte superior, negro.

Especificaciones

Applicable product family	MY2K, MY4, MY4-GS
Mounting method	DIN rail/screw
Terminal	Rise-up
Product Width (unpacked)	27 mm
Product Height (unpacked)	82 mm
Product Depth (unpacked)	42.5 mm
Color	Black
Hold down clip included	×
Release Lever included	×
Applicable ferrules	Forked terminals, Round terminals

También se ajusta a



MY4 100/110VDC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech indicator, label facility, 100/110 VDC



MY4 48/50VAC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech indicator, label facility, 48/50 VAC



MY4 48VDC (S)

Relay, plug-in, 14-pin, 4PDT, 5 A, mech indicator, label facility, 48 VDC



MY4-GS 12VAC

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 12 VAC

**MY4-GS 12VDC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 12 VDC

**MY4-GS 220/240VAC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 220/240 VAC

**MY4-GS 24VAC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 24 VAC

**MY4-GS 24VDC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 24 VDC

**MY4-GS 48VDC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 48 VDC

**MY4-GS-R AC12**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 12 VAC

**MY4-GS-R AC220/240**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 220/240 VAC

**MY4-GS-R AC24**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 24 VAC

**MY4-GS-R DC12**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 12 VDC

**MY4-GS-R DC24**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 24 VDC

**MY4-GS-R DC48**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical indicator, 48 VDC

**MY4H 100/110VDC**

Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, 110 VAC

**MY4H 110/120VAC**

Relay, plug-in, 14-pin, 4PDT, 3 A, hermetically-sealed

**MY4H 12VDC**

Relay, plug-in, 14-pin, 4PDT, 3 A, hermetically-sealed

**MY4H 24VAC**

Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, 24 VAC

**MY4H 24VDC**

Relay, plug-in, 14-pin, 4PDT, 1 A, hermetically-sealed

**MY4H 48VDC**

Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, 48 VDC

**MY4H-0 24VDC**

Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, 24 VDC

**MY4IN 100/110VDC (S)**

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, lockable push to test button, label facility, 100/110 VDC

**MY4IN 48VDC (S)**

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, lockable push to test button, label facility

**MY4IN-CR 110/120VAC (S)**

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, coil suppressor, lockable push to test button, label facility. 100/120 VAC

**MY4IN-CR-GS 220/240VAC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, coil suppressor, lockable push test button. 220/240 VAC

**MY4IN-CR-GS-R AC220/240**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, coil suppressor, lockable push test button. 220/240 VAC

**MY4IN-D2-GS 24VDC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, coil suppressor, lockable push test button, 24 VDC

**MY4IN-D2-GS 48VDC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, coil suppressor, lockable push test button, 48 VDC

**MY4IN-D2-GS-R DC24**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, coil suppressor, lockable push test button, 24 VDC

**MY4IN-GS 100/110VDC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 100/110 VDC

**MY4IN-GS 110/120VAC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 110/120 VAC

**MY4IN-GS 12VDC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 12 VDC

**MY4IN-GS 220/240VAC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 220/240 VAC

**MY4IN-GS 24VAC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 24 VAC

**MY4IN-GS 24VDC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 24 VDC

**MY4IN-GS 48VDC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 48 VDC

**MY4IN-GS-R AC110/120**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 110/120 VAC

**MY4IN-GS-R AC220/240**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 220/240 VAC

**MY4IN-GS-R AC24**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 24 VAC

**MY4IN-GS-R DC100/110**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 100/110 VDC

**MY4IN-GS-R DC12**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 12 VDC

**MY4IN-GS-R DC24**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 24 VDC

**MY4IN-GS-R DC48**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, lockable push test button, 48 VDC

**MY4IN1 100/110VDC (S)**

Relay, plug-in, 14-pin, 4PDT, reverse coil polarity, 5 A, mech & LED indicators, lockable push to test button, label facility. 100/110 VDC

**MY4IN1-D2 12VDC (S)**

Relay, plug-in, 14-pin, 4PDT, reverse coil polarity, 5 A, mech & LED indicators, coil suppressor, lockable push to test button, label facility, 12 VDC

**MY4N 100/110VDC (S)**

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, label facility, 100/110 VDC

**MY4N 110/120VAC (S)**

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, label facility, 110/120 VAC

**MY4N 48/50VAC (S)**

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, label facility, 48/50 VAC

**MY4N-CR 110/120VAC (S)**

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, coil suppressor, label facility, 110/120 VAC

**MY4N-CR-GS 220/240VAC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, coil suppressor, 220/240 VAC

**MY4N-D2 12VDC (S)**

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, coil suppressor, label facility, 12 VDC

**MY4N-D2-GS 12VDC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, coil suppressor, 12 VDC

**MY4N-D2-GS 24VDC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, coil suppressor, 24 VDC

**MY4N-GS 12VDC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, 12 VDC

**MY4N-GS 220/240VAC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, 220/240 VAC

**MY4N-GS 220VDC**

Relay, plug-in, 14-pin, 4PDT, 3 A, mechanical & LED indicators, 220 VDC

**MY4N-GS 24VDC**

Relay, plug-in, 14-pin, 4PDT, 6 A, mechanical & LED indicators, 24 VDC

**MY4N-GS 48VDC**

Relay, plug-in, 14-pin, 4PDT, 5 A, mech & LED indicators, label facility, 48 VDC

**MY4N1 24VDC (S)**

Relay, plug-in, 14-pin, 4PDT, reverse coil polarity, 5 A, mech & LED indicators, label facility, 24 VDC

**MY4N1-D2 24VDC (S)**

Relay, plug-in, 14-pin, 4PDT, reverse coil polarity, 5 A, mech & LED indicators, coil suppressor, label facility, 24 VDC

**MY4Z 110/120VAC (S)**

Relay, plug-in, 14-pin, bifurcated contacts, 4PDT, 5 A, mech indicator, label facility, 100/120 VAC

**MY4Z 220/240VAC (S)**

Relay, plug-in, 14-pin, bifurcated contacts, 4PDT, 5 A, mech indicator, label facility, 220/240 VAC

**MY4Z 24VDC (S)**

Relay, plug-in, 14-pin, bifurcated contacts, 4PDT, 5 A, mech indicator, label facility, 24 VDC

**MY4ZH 100/110VAC**

Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, bifurcated contacts, 110 VAC

**MY4ZH 24VAC**

Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, bifurcated contacts, 24 VAC

**MY4ZH 24VDC**

Hermetically-sealed relay, plug-in, 14-pin, 4PDT, 3 A, bifurcated contacts

**MY4ZIN 24VDC (S)**

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, test button, 24 VDC



MY4ZIN1 24VDC (S)

Relay, plug-in, 4PDT (bifurcated), reverse coil polarity, 3 A, mech. + LED indicator, test button, 24 VDC



MY4ZN 220/240VAC (S)

Relay, plug-in, 4PDT (bifurcated), 3 A, mech. + LED indicator, 220/240 VAC



MY4ZN 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, label facility, 24 VDC



MY4ZN-D2 24VDC (S)

Relay, plug-in, 14-pin, 4PDT, bifurcated contacts, 5 A, mech & LED indicators, coil suppressor label facility, 24 VDC



MYQ4 110/120VAC

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, 110/120 VAC



MYQ4 220/240VAC

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, 220/240 VAC



MYQ4 24VDC

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, 24 VDC



MYQ4N 110/120VAC

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, with indicator, 110/120 VAC



MYQ4N 220/240VAC

Plastic sealed relay, plug-in, 14-pin, 4PDT, 1 A, with LED, 220/240 VAC



MYQ4N 24VAC

Plastic sealed relay, plug-in, 14-pin, 4PDT, 1 A, with LED, 24 VAC



MYQ4N 24VDC

Relay, plug-in, 14-pin, 4PDT, 1 A, plastic sealed model, with indicator, 24 VDC



MYQ4N-D2 24VDC

Plastic sealed relay, plug-in, 14-pin, 4PDT, 1 A, with LED, 24 VDC



MYQ4Z 200/220VAC

Plastic sealed relay, plug-in, 14-pin, 4PDT, 1 A, bifurcated contacts

Accesorios



PYC-0

Clip metálico de retención (clip de muelle de alambre) para su uso con PYF14-ESN/ESS (solo para su uso con relés). Se vende en múltiplos de 10 por paquete; no se venden por separado).



PYC-35-B

Clip de fijación, plástico, para PYF14-ESS-B/-ES-B, se vende en múltiplos de 10 por paquete



PYC-TR

Placa de identificación para la toma P2RF-**-ESS (1 unidad = 1 bolsa incluye 10 placas)

Descargas

Librería CAD



PYF14-ESN-B Relay Sockets

Datasheet

EN PDF 600 KB

TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 20 March, 2023. Haga clic aquí para acceder a los [legal](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU