



S8VK-G24024

Fuente de alimentación 240W/24V/10A carril DIN

Type	Book type
Mounting method	DIN rail
Phase	Single
Power output	240 W
Efficiency	92 %
Output voltage	24 V
Rated output current	10 A
Power boost ratio	120 %
Temperature range	-40-70 °C
Terminal	Screw
Communication port(s)	None
Alarm function	-
Number of output branches	1
Rated supply voltage at AC 50 Hz	100-240 V
Allowable supply voltage AC	85-264 V
Allowable supply voltage DC	90-350 V
Width	60 mm
Height	125 mm
Depth	140 mm

S82Y-VK10F

Soporte de montaje frontal (para los modelos de 120, 240 y 480 W)

Productos relacionados:



Disyuntor electrónico

S8V-CP - Disyuntor electrónico



S8V-NF

Filtro de ruido S8V-NF

Descargas

Librería CAD



Perfect Power Supply Solutions

Catálogo

ES PDF 800 KB



S8VK-G Switch Mode Power Supply

Datasheet

EN PDF 10 MB



S8VK-S/S8FS-G

Catálogo

EN PDF 7 MB

TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 18 August, 2022. Haga clic aquí para acceder a los [legal](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU